



Specifications Ledvance LED
Downlight Slim Square SQ155 12W
1020lm 120D - 830 Warm White

[View Product](#)

General Information

| | |
|--------------------------|--------------------------------------|
| SKU | 233378 |
| EAN | 4058075079274 |
| Brand | Ledvance |
| Manufacturer Name | DL SLIM SQ155 12W/3000K WT IP20 LEDV |
| Any Lamp all-in warranty | 3 Years |
| Average Lifetime (h) | 30000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |
| Beam Angle (degree) | 120 |

| | |
|--------------------------|---------------------------------------|
| Luminous Efficacy (lm/W) | 85 |
| Power factor | >0.50 |
| Installation Depth (mm) | 50 |
| Unified Glare Rating | < 28 - for hallways and storage rooms |
| Optical Cover | PC (Polycarbonate) |
| Suitable for Outdoor | No |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 155x155 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +50 |
| Housing | PC (Polycarbonate) |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | PI [Push-in connector 2-pole] |
| Series | DOWNLIGHT SLIM |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 30 |
| Diameter (mm) | 169 |

Sensor Information  Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



Easy return process